

# BONDEX WPC CLEANER CONCENTRATE

10140DSC44X96



## 1. PRODUCT DESCRIPTION

1.1	Product type	Effective cleaner, which removes even the most stubborn dirt. Ideal pre-treatment for BonDEX Impregnation. Especially developed for wood-plastic composites (WPC). Refreshes the surface and preserve the natural appearance. Acts antistatically. (Please note that WPC is not a generic and uniform material, but depends on quality of raw materials and manufacturer).
1.2	Manufacturer / Distributor	PPG Coatings Danmark A/S, Gladsaxevej 300, DK-2860 Søborg, Denmark. Tel.: +45 39 57 93 00 - www.bondexwood.com
1.3	Where to use	On wood-plastic composites (WPC)
1.4	Product effect	Bondex WPC Cleaner removes dirt, lime, bird droppings, environmental deposits, greasy and oily impurities, and is a special cleaning agent designed for e.g. decking made from WPC.
1.5	Form supplied	Ready to use.
1.6	Can sizes	1.00 L

## 2. TECHNICAL DATA

2.1	Density	1.0 g/ml.
2.2	Viscosity	Liquid.
2.3	pH value	9-10.
2.4	Odour	Odourless.
2.5	Dilution	Mix with water - see 3. Application.
2.6	Consumption	Very economical.
2.7	Additives	Ingredients as per Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents: <5% anionic surfactants, <5% nonionic surfactants methylchloroisothiazolinone, methylisothiazolinone, fragrances, limonene, citronellal.
2.8	Storage	Store and transport frost free in tightly closed container.
2.9	Shelf life	Can be kept in unopened containers for several years. Close containers securely after use.

## 3. APPLICATION

3.1	Stains or heavy soiling	Add approx. 200 ml to a 10 litre bucket (mixing ratio: 1:50) of warm water. Apply with a floor mop or damp cloth. Go over the area with a scrubbing brush or stiff-bristled brush and pick up dislodged dirt. Finally, wipe with clean water.
-----	-------------------------	---

	Maintenance cleaning	Add approx. 50 ml to a 10 litre bucket (mixing ratio: 1:200) of warm water and mix well. Wipe with a floor mop or cloth and leave to dry. There is no need to wipe over afterwards. Using Bondex WPC Cleaner is not a substitute for the annual surface treatment of WPC surfaces. If you wish to apply a protective treatment to the surface, treat with Bondex Impregnation once dry.
3.2	Application instruction	Shake well before use. Not suitable for application and drying at temperatures below +10°C and/or relative humidity of >80%. Ensure that all of the product used on a single surface has the same batch number.
3.3	Cleaning of tools	Warm water.

#### 4. SAFETY PRECAUTIONS

4.1	In general	Common safety rules for work with paints and varnishes must be observed. Further information is available from our Material Safety Data Sheet.
-----	------------	--

#### 5. GOOD ADVICE

5.1	Good advice	Do not empty into drains or into the environment. Product waste must not be poured into the sewers, water reserves or soil. Do not store in rooms where food is prepared or stored. Only store in original container. Do not mix or use Bondex WPC Cleaner with other cleaning agents. Empty can may be recycled (check with your local waste disposal site or your local authorities).
-----	-------------	---

The purpose of this Technical Data Sheet is to provide our clients with information about the properties and characteristics of the product. The information provided is based on tests conducted by us under usage conditions that comply with the prevailing standards. Our recommendations for use are for information only, and in no event shall they take precedence over any specific recommendation, taking into account the nature and conditions of a particular site, nor shall they engage PPG's liability. Before all applications of the product, clients should check that this document has not been amended by a more recent version, which takes into account new technical data. This version annuls and replaces all previous versions of Technical Data Sheets relating to this product.