

BONDEX WOOD CLEANER

WOOD, STONE, CONCRETE, GLASS, CERAMIC

EXTERIOR



1. PRODUCT DESCRIPTION

1.1	Product Code	10140DSC44X93
1.2	Product type	Cleaning agent for removal of dirt and incrustations.
1.3	Manufacturer	PPG Coatings Denmark A/S, Export Department, Gladsaxevej 300, DK-2860 Søborg, Denmark. Tel.: +45 39 57 93 00 - E-mail: export@ppg.com - Web: www.bondexwood.com
1.4	Where to use	Can be used on various types of wood, e.g. cladding, wooden decks, fences, garden furniture etc, stone, concrete, glass, ceramic. Also suitable for use on mineral surfaces, such as mortar, masonry and flagstones. Test colour fastness or discolouring of metal components on the surface to be treated on a non-visible are, before the actual treatment. Apply a test coat on the surface to be treated, as various cleaning effects are achieved depending on the surface properties.
1.5	Form supplied	Concentrate - dilute 1:9 with water

2. TECHNICAL DATA

2.1	Active ingredients	10% benzalconium chloride.
2.2	Solvent	Water.
2.3	Pigments	Bluish in the packaging. Will appear colourless during application and drying.
2.4	Density	App. 1.0 g/ml.
2.5	Viscosity	Thin liquid.
2.6	Thinning	1:9 with water
2.7	Coverage	App. 2-5 m ² /l, depending on wood species and the the state of the substrate.
2.8	Drying time	Exposure time app. 48 hours.
2.9	Storage	Store and transport frost free in cool and dry environment out of direct sunlight.
2.10	Shelf life	5 years in unopened container. Limited shelf life after opening.

3. TREATMENT

3.1	Tools	Brush, watering can or garden sprayer.
3.2	Application method	Apply with brush, watering can, garden sprayer. During application and drying, temperature must be above 5°C and the relative humidity below 80%
3.3	Treatment	Remove loose dirt and thick layers of incrustations. Dilute BonDEX Wood Cleaner 1:9 with water. Apply an even layer on a damp surface. Leave the liquid to work for a couple of days. Then brush surface with a brush with stiff bristles. If the attack is severe, you can dilute BonDEX Cleaner 1:3 with water. When the surface is dry (max 15 + 3% humidity), you can apply top coat.
3.4	Cleaning of tools	Soap and water.

5. SAFETY & ENVIRONMENT

5.1	In general	Common safety rules for work with paints and varnishes must be observed. Further information is available from our Material Safety Data Sheet.
5.2	Disposal	Do not empty into drains or into the environment. Do not pour product waste into the sewers, water reserves or soil. Hand in left over product at your local waster disposal. Empty can may be recycled.

The purpose of this Technical Data Sheet is to provide our clients with information about the properties and characteristics of the product. The information provided is based on tests conducted by us under usage conditions that comply with the prevailing standards. Our recommendations for use are for information only, and in no event shall they take precedence over any specific recommendation, taking into account the nature and conditions of a particular site, nor shall they engage PPG's liability. Before all applications of the product, clients should check that this document has not been amended by a more recent version, which takes into account new technical data. This version annuls and replaces all previous versions of Technical Data Sheets relating to this product.