



BONDEX

BONDEX Extreme Decking Oil

World Class
Wood Protection

NEW



Dyrup A/S
Gladsaxevej 300
DK-2860 Søborg
Denmark
Tel: +45 39 57 93 00
www.dyrup.com

Bondex® is a registered trademark
Copyright© Dyrup A/S - March 2012

 DYRUP

DOUBLE DURABILITY!

Extremely quick drying - you can walk on the treated area after just 1 hour

BONDEX Extreme Decking Oil

- Water based protective and nourishing oil for outdoor wooden decking
- The original glow of the wood is preserved
- The oil gives a water repellent property to the wood
- Resists mould and fungal growth
- Excellent weather protection
- Lasts twice as long as conventional decking oils




Available in 5 translucent colours + clear



722 Oak



668 Red Mahogany



725 Palisander



731 Nut Brown



729 Teak



900 Clear



Protects against mould



Double durability
Hard wearing



Water repellent



Coverage:
app. 15 m²/l

Give your deck the right care

A wooden deck is a horizontal surface. For this reason it is highly exposed to dirt and wear, sun and water. In order to keep a wooden deck looking healthy and nice, it needs maintenance more often than other kinds of wood work.

A wooden deck must be given the same pre-treatment as other wooden surfaces. As end treatment you obtain the best result and protection with BonDEX Extreme Decking Oil, which is quickly absorbed into the wood. BonDEX Extreme Decking Oil enhances the glow of your wood and gives you a beautiful result, while at the same time protecting against mould and incrustations on the surface.

Useful tips

- ! New and untreated wood should not be left without treatment for very long. The natural degradation of the wood starts the very first day the wood is left outside. We recommend that you apply BonDEX Decking Oil within the first 2 weeks.
- ! Make sure that the wood is clean and dry - the moisture of the wood should not exceed 18% at the time of application.
- ! Remove knots and/or dirt, mould or resin and wipe off the surface with a lint free cloth moistened with alcohol.
- ! If the wood has already been attacked by mould or has incrustations, you must clean with a suitable detergent before applying BonDEX Extreme Decking Oil. Highly weathered areas must be sanded down to healthy wood.
- ! Repeated treatment with a pigmented decking oil will make the colour of the wood go darker over time. In order to avoid this, you can mix a coloured product with the colour Clear 1:1. Never use Clear alone as the end treatment.
- ! If you have treated your wooden deck previously with a solvent or water based decking oil, you must ensure that the previous layer of decking oil is weathered down before applying a new coat, as the decking oil with otherwise not adhere properly to the surface. So make sure that the surface is almost free from previous wood protection treatments.

Also suitable for exotic wood species such as teak, nyatoh, bangkirai, meranti and ipe.

