



## BONDEX CHALK PAINT

- For the individual design of untreated pieces of furniture.
- Gives pieces of furniture a shabby chic look
- Can also be used as a decorative covering coat in special shades.

---

### 1. general description

- 1.1 Product name BONDEX CHALK PAINT
- 1.2 Manufacturer PP Coatings Deutschland GmbH.
- 1.3 Product Type Aqueous chalk paint
- 1.4 Application Inside:  
For pieces of furniture, wood paneling, picture frames, etc.
- 1.5 Product Effect Serves as a primer/top coat for further design with Bondex finishing wax.
- 1.6 hue Cozy green, soft blue, soft grey, creative white, happy green, charming white, romantic pink, sandy brown, cozy grey, stone grey, elegant taupe, creamy vanilla, cozy purple, antique red, cozy petrol, warm brown.
- The color effect is determined by the type and color of the wood. Before use, we recommend a test coat, later complaints cannot be accepted.
- 1.7 form of delivery anti-drip. Ready to process.
- 1.8 Packaging 0.50 liters
- 1.9 test mark -

---

### 2. Composition / Properties

- 2.1 binder alkyd
- 2.2 solvent Water.
- 2.3 Odor low odor Odorless after drying.
- 2.4 Consumption approx. 80 ml/m<sup>2</sup> .1 liter is sufficient for approx. 12 m<sup>2</sup> . Determine exact quantity by trial order.
- 2.5 Drying Time Dust-dry after approx. 30 minutes (at 23°C/ 60% relative humidity). Can be painted over after approx. 4 hours. At low temperatures and/or high humidity, the drying time is extended. trial coating execute.
- 2.6 Dilution Use undiluted. Ready to use.
- 2.7 shelf life Can be kept for approx. 2 years in unopened containers. Close the container tightly after use and briefly turn it upside down. Store and transport cool, dry but frost-free.
-



## BONDEX CHALK PAINT

---

### 3. underground

- 3.1 underground type Wood, raw / untreated.
- 3.2 Ground condition The substrate must be dry, clean, stable and free of grease, oil and wax.
- 3.3 Pre-treatment Scrape out resin areas and use a suitable agent, eg nitro thinner to clean. Remove dirt, grease, wax, mold and loose paint. Resin leaks cannot be prevented with technical coating measures. Moisten raw wooden surfaces with warm water (sponge) and allow to dry before sanding. Then, if necessary, smooth the wood fibers with fine sandpaper. Remove sanding dust. Do not sand wooden surfaces with steel wool. Risk of rust staining. Do not use on bleached wood containing oxalic acid.
- 3.4 wood moisture max 18%

---

### 4. processing

- 4.1 application process brush, roller.
- 4.2 Processing Notes Stir well before use. Do not process and dry at temperatures below + 15°C and/or relative humidity > 80%. In order to guarantee the same colour, only use material with the same batch number. process on a surface. Wood ingredients sometimes soil adjacent surfaces or stone floors (dark or colored offshoots). They are washed out over end-grain wood surfaces. Therefore, treat end-grain (ends and interfaces) with additional coats until the fibers are saturated. After the first coat, wood fibers can stand up. A smooth surface is achieved with a light intermediate sanding. Characteristics typical of wood, such as discoloration caused by substances contained in the wood and changes in the color of modified wood, cannot be avoided by the treatment. Door seals must be acrylic resistant. Risk of plasticizer migration. If in doubt, consult the seal manufacturer and replace.
- 4.3 Application Depending on the desired surface effect, treat 1 - 2 x with Bondex Vintage Paint. The color result depends on the tools used (brush, roller), the amount of product used, the nature and pre-treatment of the wood. Not suitable for coating windows.
- 4.4 Shabby chic look After drying, wear another Bondex once. chalk paint on. After drying, treat the wood surface with stainless steel wool or sandpaper, as required. Then apply the Bondex Finishing Wax with a cloth once or in several layers.
- Regularly inspect the finished wood surfaces. Repair small damages immediately - this extends the durability.**
- 4.5 Cleaning of tools Immediately after use with soap and water.



## BONDEX CHALK PAINT

---

### 5. Security / Disposal

For safety advice and disposal information, please refer to the safety data sheet.

---

### 6. General notes

Product code: BSW 20.

Do not place any hot objects (e.g. pots, coffee cups, etc.) on the treated area. Keep away from food, drink and animal feedingstuffs.

Store only in original containers.

---

The purpose of this leaflet is to provide serious, but non-binding, advice on the possible uses of Bondex Vintage Paint. The technical information is based on years of experience, but does not release the consumer from checking Bondex Vintage Color for the intended purpose. Due to the variety of possible uses and processing, however, binding nature and liability must be excluded. If in doubt, please contact our representatives, our field staff or our application technology department directly. Calling in our specialist consultants does not establish a consulting relationship. When this leaflet is published, the previous one loses its validity.